I.



| | Product Specifications |
|--|---|
| | Design |
| | Meets/Exceeds ASME B40.100 |
| LEWINE RATURE | Accuracy |
| | ±3/2/3% (ASME Grade B) |
| WAR WAR | Dial Size(s) |
| | 3 ½" Diameter (89 mm) |
| | Case |
| | Steel, Black Painted |
| | Bezel |
| | Steel, Black Painted |
| | Tube & Socket |
| | Copper Alloy |
| | Movement |
| | Brass |
| | Connection |
| lavah Instrumenta Tridicatora ara durahla, anat affantina ang binatina ang ang | 1/4 NPT - Center Back Mount |
| larsh Instruments Tridicators are durable, cost-effective combination pressure | Pressure Ranges |
| nd temperature instruments for use in a wide variety of commercial and | 60 to 300 psi (130-680 Ft H ₂ 0) |
| idustrial boiler and hot water applications. | Temperature Ranges |
| | 60° to 260°F (20° to 120°C) |
| eatures: | Standard Scale |
| Rotatable Set Pointer | Dual Scale Celsius and Fahrenheit |
| | Dial Color |
| • 2 1/2" & 3 1/2" Sizes Optional | Black Markings on White |
| | Pointer |
| | Aluminum, Red Painted with Black Painted Set Pointer |
| Product Dimensions | Window |
| | Acrylic |
| | Vent Plug |
| | N/A |
| | Weight |
| Red Pointers | 2.0 lb. |
| | |
| Dial, White with \square Black Characters $ $ 1.06 $$ $ $ 875 $$ 1. | 0/ |
| | 74 |
| | |
| | |
| | |
| | 0.312 OD |
| | ↓ |
| | |
| | |
| | ↑ |
| | Dulh |

%₁₆ Square -

¹/4 NPT

— Bulb